ORDINANCE NO. 11-

AN ORDINANCE ACCEPTING A BID FOR A POWER RAKE

WHEREAS, the Village obtained bids for a Power Rake; and

WHEREAS, the Public Works Committee met to review the bids and is recommending the bid from German Bliss, at an estimated price of \$8,378.13, and,

NOW, THEREFORE, BE IT ORDAINED BY THE PRESIDENT AND BOARD OF TRUSTEES OF THE VILLAGE OF CHATHAM, ILLINOIS, AS FOLLOWS:

SECTION 1: That the bid from German Bliss for an estimated cost not to exceed \$8,378.13 per Exhibit A attached hereto is hereby approved.

SECTION 2: The Village Manager is hereby directed to complete the necessary documents at the appropriate timing.

SECTION 3: This Ordinance is effective upon its passage and approval.

Thomas S. Gray, President Village of Chatham

ATTEST:

AYES: SHEAR MAN BOYLK REYNOLDS KAVANAGE PASSED:

NAYS: 0 APPROVED

ABSENT: KAVANACH APPROVED:

of CHATA

The Village of Chatham will be accepting sealed bids for the following Items.

8500# reel trailer

Vacuum trailer
Power Rake

The Bid packets are a meet or exceed specifications.

Additional information: A demonstration model for the vacuum trailer will be acceptable as long as the unit has 150 hr's or less and still has factory warranty. All sealed bids must be returned by 1:00pm March 21 2011. Any and all bids received after 1:00pm on March 21 will be considered unacceptable and will be removed from the opening. The Village of Chatham reserves the right to accept and or reject any and all parts of the bid.

ALL BIDS MUST BE SEALED AND MADE OUT TO:

VILLAGE OF CHATHAM

116 E. MULBERRY

CHATHAM IL. 62629

SEALED BID: (EQUIPMENT BEING BID)

ATTENTION SHANE HILL

Any Questions please call Shane 217-652-5038

Power Rake Bid Specifications	· Meets or exceeds		
	Yes	No	
Working Width: 90"			
Mounting Type (Three Point Hitch) Power Take Off Drive Lines/Clutch: Min Of Cat 3 Drivelines with slip-clutch on secondary driveline	•		
ROLLER Desighn: Minimum 9-38" Diameter with 3/4" x 1-1/2" Carbide tipped studs			
Angling: Minimum 15 degree Hydraulic angle Both Left and Right	 		
Gauge wheels: Minimum 2 gauge wheels. Size 16.5" \times 6.5" pneumatic tires with sealant installed.			
End Plates: Rake is equipped with removableend plates for moving dirt.			
End plates can be stored on the rake when not in use.			
Chain Drive: minimum of #50 Double continuous roller chain that is enclosed in oil bath.	<u>, , , , , , , , , , , , , , , , , , , </u>		
Skid Shoes: Standard and Replacable			
Gear Box: 540RPM, Cast Iron Housing.			
Gear Box Warranty: Minimum of 5 yr		<u> </u>	
Machine Weight: Min of 1125lbs working weight.			

. !

.

GERMAN-BISS —EQUIPMENT—— 1-800-SATISFIED

Customer Name VIII AGE OF ChATHAM Date 3/15/2011 Quote Valid for Address III E Mulberry Phone # 217-652-5038 City, State, Old H.	30	đays
Address III. F. Mulh Frank Phone # 217 - 652 - 5038		
City, State, Chatham, IL 62629 Salesman Gail Shawle	·	
DESCRIPTION	PRICE	
LANDEIDE PR 1690-0221 90"		83.78.13
CARDIDE TIP HYDRAULIE ANGLING POWER RAKE		
POWER RAKE		
		. 2 Signe
	í	
		~
		
	-	·
	<u> </u>	
	-	
	 	
	1	
	 	
	Total	
TRADE-IN	ALLOS	VANCE
11000=114	ALLO	PAIRCE
ì		
<u> </u>	 	
<u></u>		-
SUBTOTAL:		
MISCELLANEOUS		
	<u> </u>	<u>-</u>
Sales Tax AG Exempt 7: NO Yes	<u>-</u>	
Extended Warranty	**** **,	
License & Title	 	
Filing/Doc Fees		
Delivery Charges		
_	020	18 13
TOTAL	^ 7 /	1 1 1 1

Power Rake Bid Specifications

- · Working width: 90 inches
- Mounting type: Three Point Hitch
- Power Take Off Drive Lines/clutch: Minimum of Cat. 3 drivelines with slip-clutch on secondary driveline.
- Roller Design: Minimum 9-3/8" Diameter with ¾" x 1-1/2" Carbide Tipped Studs.
- Angling: Minimum 15 degree hydraulic angle both left and right angle.
- Angle Cylinder: Minimum 2" x 8" hydraulic cylinder.
- Gauge wheels: Minimum 2 gauge wheels. Size: 16.5" x
 6.5" Air Tires with Tire Sealant installed.
- End Plates: Rake is equipped with removable end plates for moving dirt. End Plates can be stored on the rake when not being used.
- Chain Drive: Minimum of #50 Double continuous roller chain that is enclosed in oil bath.
- Skid Shoes: Standard and replaceable style.
- Gear Box: 540 RPM, Cast Iron Housing
- Gear Box Warranty: Minimum of 5-year warranty
- Machine Weight: Minimum of 1125 lbs working weight.

Power Rake Bid Specifications Meets or exceeds Yes No Working Width: 90" Mounting Type (Three Point Hitch) Power Take Off Drive Lines/Clutch: Min Of Cat 3 Drivelines with slip-clutch on secondary driveline ROLLER Desighn: Minimum 9-38" Diameter with 3/4" x 1-1/2" Carbide tipped studs Angling: Minimum 15 degree Hydraulic angle **Both Left and Right** Gauge wheels: Minimum 2 gauge wheels. Size 16.5" x 6.5" pneumatic tires with sealant installed. End Plates: Rake is equipped with removableend plates for moving dirt. End plates can be stored on the rake when not in use. Chain Drive: minimum of #50 Double continuous roller chain that is enclosed in oil bath. Skid Shoes: Standard and Replacable Gear Box: 540RPM, Cast Iron Housing. Gear Box Warranty: Minimum of 5 yr

Machine Weight: Min of 1125lbs working weight.



Quote ld: 5241314

Prepared for: Village of Chatham

Proposal for: Village of Chatham

Prepared By: DOUGLAS GIBSON

SLOAN IMPLEMENT COMPANY 1600 N SPRINGFIELD STREET

VIRDEN, IL 62690 Phone: 217-965-3333

Fax: 217-965-3335

Work Email: DGIBSON@SLOANS.COM

Date: March 14, 2011 Offer Expires: April 25, 2011



Quote ld:5241314

March 14, 2011 Village of Chatham IL

DOUGLAS GIBSON 217-965-3333 SLOAN IMPLEMENT COMPANY

Power Rake Bid Specifications	Meets or exceeds
	Yes No
Working Width: 90 ⁿ	<u> 1x84"</u>
Mounting Type (Three Point Hitch)	X Wender 35E
Power Take Off Drive Lines/Clutch: Min Of Cat 3	
Drivelines with slip-clutch on secondary driveline	
ROLLER Desighn: Minimum 9-38" Diameter with 3/4" x 1-1/2" Carbide tipped studs	X
Angling: Minimum 15 degree Hydraulic angle Both Left and Right	<u>X</u>
Gauge wheels: Minimum 2 gauge wheels. Size 16.5" x 6.5" pneumatic tires with sealant installed.	<u>X</u>
End Plates: Rake is equipped with removableend plates for moving dirt.	X
End plates can be stored on the rake when not in use.	X
Chain Drive: minimum of #50 Double continuous roller chain that is enclosed in oil bath.	X
Skid Shoes: Standard and Replacable	Land y Barbotoms assired X L
Gear Box: 540RPM, Cast Iron Housing.	
Gear Box Warranty: Minimum of 5 yr	1 X I YR WATTANTY
Machine Weight: Min of 1125lbs working weight.	1260lbs

Speed + Bio Price Included

JOHN DEERE

SLOAN IMPLEMENT COMPANY 1600 N SPRINGFIELD STREET VIRDEN, IL 62690

Phone: 217-965-3333 Fax: 217-965-3335

Quote ld: 5241314

Salesperson: X_

	Quote Summary				
Prepared For: Village of Chatham IL Home: 217-652-5038	Prepared By: DOUGLAS GIBSON 1600 N SPRINGFIELD STREET VIRDEN, IL 62690 DGIBSON@SLOANS.COM	Quote Id Created C Last Mod Expiration	on: N	n :Marc	4, 2011 :h 14, 2011
Equipment Summary	Selling F	Price	Qty		Extended
FRONTIER PR1184	\$ 8,484.	.47 X	1	=	\$ 8,484.47
Equipment Total					\$ 8,484.47
	Quote 9	Summary			
	Equipm	ent Total			\$ 8,484.47
	SubTota	al			\$ 8,484.47
	Total				\$ 8,484.47
	Down P	ayment			(0.00)
	Rental A	Applied			(0.00)
	Balanc	e Due			\$ 8,484.47

Accepted By : X _____



Selling Equipment

Quote Id: 5241314

	FRONTIER	R PR1184		
				Selling Price \$ 8,484.47
Code	Description	Qty	Unit	Extended
Power Rake	PR1184 Landscape Power Rake	1	\$ 11,573.00	\$ 11,573.00
	Discount		\$ -3,088.53	\$ -3,088.53
Total				\$ 8,484.47

PR1184 - 84 In. Power Rake

Function: Landscaping and

Site Development
Hitch Compatibility:
Category I, Category II,

iMatch, Quick Coupler Compatible

Rotor: Cylindrical with
Welded Carbide Teeth
Carbide Teeth per Rotor: 132
Depth Control: Dual Independently
Adjustable Gauge Wheels

Gauge Wheel Description: 16.5 x

6.5-8

Gauge Wheel Height Adjustment:

Manual Split Clamp

Angle Adjustment: Hydraulic Hydraulic Cylinder Manufacturer:

Best Metal Ind.

Hydraulic Cylinder Description:

2.00 In.

Bore 1.25 In. rod 8.00 In. Stroke Working Angles R or L: 0-15 Degrees

Height: 44 In.

Transport Width: 93 In. Working Width: 84 In.

Working Width at Maximum Angle: 81

In.

Roll-Back Barrier Range: 5/16 In. to 4-11/16 In.

Length: 70 In.

Side Drive: Chain ASA 60-2H

Chain Case Lube:

Cenex 365 #00 Fluid Grease

Tubing Size: 4 In. x 4 In.

Tubing Wall Thickness: 5/16 In. Tractor PTO Speed (RPM): 540 Driveline Manufacturer: Weasler

→ Primary Driveline Description: 35E Secondary Driveline Description:

44E with

Friction Clutch (1-3/4 In. 20

Splines)

Clutch/Torque Setting (Number):

1695

Tractor PTO HP Requirements
Minimum-Maximum: 42-80 HP
Tractor Hydraulic Requirements:

1500 PSI

Gearbox Manufacturer: Superior

Gearbox Description:

Straight Bevel Gear in Oil Bath

Gearbox Oll Recommendation: 85-90W

Gearbox Reduction: 2:1
Rotor Speed (RPM): 270
Rotor Direction of Rotation:

Against DOT

Approximate Operating Weight: 1260

lbs.

Approximate Shipping Weight: 1700

lbs.

Parking Stand: Standard Approximate Set-Up Time:

60 Minutes
Warranty: 1 Year

Specifications are based on published information at the time of publication. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Specifications are subject to change without notice. Contact <u>your local John Deere dealer</u> for more detailed information.

Prices are subject to change without notice. In all cases, current published price lists and incentive program bulletins will take precedence.

Chain drive

Print

The oil-bathed enclosed chain drive with center chain idler is proven to prolong drive chain life by eliminating chain slip and compensating for chain stretch. The low-profile chain case allows for maximum teeth and roller depth on the PR11 Series Power Rake.

Provide feedback about this page

Last Updated: 14-May-2010



Dealer Menu Feedback Help

Competitive Specs

Specs | Compare Specs | Compare All

MANUFACTURER MODEL		Frontier PR1184
Dimensions		
	Machine length, in. (cm)	70 (177.8)
	Machine height, in. (cm)	44 (118.8)
	Transport width, In. (cm)	93 (236.2)
	Working width, in. (cm)	64 (213.4)
	Working width at max angle, in. (cm)	81 (205.7)
Welght		d r
	Operating, lb (kg)	1,260 (571.5)
	Shipping, ib (kg)	1,700 (771.1)
Tractor compatibli	ity	
	PTO horsepower, hp (kW)	42-80 (31.3-59.7)
	PTO speed (rpm)	540
	Hydraulic requirement (psi)	1500
Hitch		•
1	Compatibility	Cat. 1, Cat. 2
	Match™ compatible (Cat. 1)	Yes
	Quick coupler (Cat. 2)	Yes
Rotor		
	Speed (rpm)	270
1	Direction of travel	Against DOT
	Quantity of carbide teeth per rotor	132
Working angles		
i	Degrees left or right	0-15
Parking stands	.41	
;	Standard	Yes ·
Depth control		P.
	Туре	Dual Independent adjustable guage wheels
Set-up time		
l	Labor hours	1
Warranty		

Specifications are based on published information at the time of publication. Specifications are subject to change without notice. Contact <u>your local John Deere dealer</u> for more information.

Prices are subject to change without notice. Prices are in dollars and only applicable to products sold in the United States. In all cases, current published price lists and incentive program bulletins will take precedence. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted.

Copyright @ 1996-2010 Deere & Company. All Rights Reserved.

Privacy | Legal